



Nm¹ THE NEWTON MICROSCOPE

THE LATEST IN PORTABLE FIELD MICROSCOPY

Nm1 400

Nm1 600

Nm1 1000



For detailed information on the Newton visit newtonmicroscopes.com

The optical system is based on the RMS standard, and offers the traditional range of objective magnifications and eyepiece interchangeability.

To achieve a compact form the microscope has an inverted monocular format and uses miniature objectives, three dimensional folded optics, simplified mechanics, and a built in LED

illumination system. To extend general usability the Nm1 can be tripod mounted for bench operation, XY or slide clips attachable, and digital camera and smart phone attachable.

GENERAL SPECIFICATION

Monocular inverted

3D folded optical path

RMS standard path length and eyepiece fitment

Miniature objectives design

0.17mm cover slip corrected

Objective carrier up to x3 mounts

Standard fitment x10 N/A 0.25, x40 N/A 0.65

Optional third objective x60 N/A 0.80, or x100 oil N/A 1.25 - factory fit only

Standard eyepiece fitment x10 wide field

Variable illumination output

Internal power 3 x AAA battery pack

Battery life approx 300 hours at maximum continuous power

x2 standard tripod mounting bushes

XY slide indexer and slide clip attachments

Cavity (fluids) slide supplied as standard

Smart phone and DSLR camera attachable

Die-cast and machined optical chassis

Hardened bearing surfaces

Die-cast Aluminium stage

Injection moulded rubber coated PC/ABS case

Weight - Minimum 480grams (Nm1 400 with slide clips and USB power source connected)

Size (main body) – Length 133mm, width 110mm, height 49mm

Size (max overall) – Length 154mm, width 122mm, height 66mm

OPTICAL SPECIFICATION

MIRRORS

Precision ground 2.0 mm glass

Front silvered and coated

Surface accuracy, mirror No1 = 3-4 fringes

Surface accuracy, mirror No2 and No3 = 5 fringes

OBJECTIVE LENSES

Achromat

Precision ground Schott glass

Multi-coated

Laser aligned

Plated brass mounts

CNC machined hard anodised aluminium lens turret.

Corrected for 0.17mm cover slip

x10 N/A 0.25

x40 N/A 0.65

x60 N/A 0.80

x100 oil N/a 1.25

OPTICAL CHASSIS AND FOCUS CARRIAGE

Precision high pressure die-cast Aluminium alloy

CNC machined mirror mounts: Linear +/- 0.1mm, angular +/-0.25 degrees

CNC machined bores and shafts: Diametric +/- 0.015mm.

Fully hardened Rotational and sliding bearing surfaces

General surfaces aluminium oxide pressure blasted and black anodised

CONTROLS & FEATURES TOP

1 ILLUMINATION ► The illumination source is a built in white LED. The LED is located in an adjustable arm that positions the beam directly over the specimen. The arm can be incrementally raised or lowered for various dark ground illumination effects, or swivelled completely up to the vertical to allow clear access to the stage. The LED is switched on using the illumination button. A single press for on, and a single press for off. The LED will automatically switch off after approximately 15 minutes, and the light can be switched on again with a single button press. The timer is bypassed when an external power source is used and allows continuous illumination at the control of the button. The viewing brightness can be controlled by rotating the thumb wheel underneath for increased or decreased intensity



in the direction indicated by the graphic. Higher magnifications require higher lighting levels. Beware that at x10 the illumination needs to be pre set to the lowest level before viewing to avoid discomfort from over-brightness. Further reduction in brightness can be achieved by lifting the lighting arm slightly. Generally the lowest lighting level is sufficient for the x10 and x40 objectives, and a fresh top grade battery pack can deliver over 1000 hours illumination. At maximum power battery life will be reduced by up to 70%
2 FOCUS ► The Focus control wheel is an endless bi-rotational control, delivering the full focus range within a single 360 rotation in either direction. Focus therefore can be achieved quickly regardless of which direction the wheel is turned.
3 SLIDE CLIPS ► Micrometer XY slide indexer fitted as standard, attachable slide clips supplied.

CONTROLS & FEATURES BASE

4 MAGNIFICATION ▶ The Nm1 can carry up to 3 objectives and is available in the following configurations:

Nm1 400 = x10 and x40 objectives fitted

Nm1 600 = x10, x40, and x60 objectives fitted

Nm1 1000 = x10, x40, and x100 objectives fitted

Objective positions are numbered 1 to 3. Position 1 is x10, position 2 is x40 and position 3 is the expansion option which may be a blanking plug, a x60 or x100 objective depending on the Newton model. The magnification power is marked on the top of each objective using standard colour-coding conventions. Objectives are selected by rotating the magnification knob located in the centre of the underside of the microscope. This may be rotated in either direction and the selected objective should lightly click into position when the two red dots are aligned.



5 ILLUMINATION BRIGHTNESS ▶

The viewing brightness can be controlled by rotating the thumb wheel underneath for increased or decreased intensity in the direction indicated by the graphic.

6 EXTERNAL POWER ▶ It is possible to use external power sources to drive the lighting system instead of relying on the internal battery pack. External power sources can also create a slightly brighter light if required. The supplied USB cable connects into the socket in the side, and can be driven from a PC or a USB mains plug adaptor (often found on mobile phone chargers and also on iPod/iPhones). When using external power sources the automatic cut out is overridden.

7 MOUNTING ▶ The newton is intended primarily as a hand held device, but tripod mounting can ease photography and also reduce fatigue potential over long periods of examination. After testing many tripods we recommend the Cullman Nanomax 200T

